

model	Long mm	Wide mm	high mm	L mm	Interface	Power W	Flow M3/H
CSL-1RL/UV	1630	120	330	1365	DN50	150	5-10
CSL-2RL/UV	1630	140	350	1330	DN80	300	10-20
CSL-3RL/UV	1630	140	380	1310	DN80	450	20-30
CSL-4RL/UV	1630	160	400	1310	DN80	600	30-45
CSL-5RL/UV	1630	220	480	1280	DN100	750	45-60
CSL-6RL/UV	1630	220	480	1280	DN100	900	60-70
CSL-7RL/UV	1630	220	480	1245	DN125	1050	70-80
CSL-8RL/UV	1630	220	480	1245	DN125	1200	80-90
CSL-10RL/UV	1630	230	490	1245	DN150	1500	90-120
CSL-12RL/UV	1630	260	550	1245	DN200	1800	120-140
CSL-14RL/UV	1630	260	550	1245	DN200	2100	140-160
CSL-16RL/UV	1630	280	590	1190	DN225	2400	160-180
CSL-18RL/UV	1630	280	590	1190	DN250	2700	180-200
CSL-20RL/UV	1630	300	610	1190	DN250	3000	200-230
CSL-22RL/UV	1630	300	610	1190	DN300	3300	230-250
CSL-24RL/UV	1630	370	700	1155	DN300	3600	250-280
CSL-30RL/UV	1630	426	700	1155	DN300	4500	300-350

**High intensity ultraviolet sterilizer note: shell material SS304, overflow material SS316L**

